



Eupen, 22/04/2009

TECHNICAL SPECIFICATIONS

| | Target value | Unit | tolerance |
|--|-----------------------------------|-------------------|------------|
| Foam type | F/ | | |
| Color | white / grey-blue / anthr. | | |
| Width | 200 | cm | +2/+4 cm |
| Height | 102 | cm | -0/+5 cm |
| Color | white | | |
| Width | 205 | cm | +2/+4 cm |
| Height | 94 | cm | -0/+5 cm |
| Density gross | 40,0 | kg/m ³ | +/- 5 % |
| Density net | 38,0 | kg/m ³ | +/- 5 % |
| Compression hardn. 25% | 220 | N | +/- 10 % |
| ISO 2439-1998 40% | 260 | N | +/- 10 % |
| 65% | 500 | N | +/- 12,5 % |
| Tensile strength ISO 1798-1997 | 100 | Kpa | min. |
| Elongation at break ISO 1798-1997 | 160 | % | min. |
| Compression load deflection ISO 3386-1 | 6,00 | Kpa (40%) | +/- 10 % |
| Compression set ISO 1856-2000 | 3,0 | % | max. |

Our foam types are free from CFC, HCFC and Formaldehyde.

J.-P. Doeuillet
Qualityoffice